

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**· Trade name: **P962 1K ISOLATOR**

· Article number: B433

· UFI: M6G0-U0EP-4007-WTW3

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9b Fillers, putties, plasters, modelling clay

· Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· Environmental release category ERC2 Formulation into mixture

· Article category AC1 Vehicles

· Application of the substance / the mixture Surface protection

**1.3 Details of the supplier of the safety data sheet**

· Manufacturer/Supplier:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 &amp; MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

· Further information obtainable from:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 &amp; MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

**1.4 Emergency telephone number:**

Regional Medicines and Poisons Information Centre NI

Pharmacy Department, Royal Hospital Suite

Grosvenor Road Belfast

Telephone: +44 28 90 63 2032

Fax: +44 28 90 24 80 30

Emergency telephone: 844 892 0111

E-mail address: nirdic.nirdic@belfasttrust.hscni.net

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

**Trade name: P962 1K ISOLATOR****SECTION 2: Hazards identification****2.1 Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

**2.2 Label elements**

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

propan-2-ol

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**2.3 Other hazards**

Results of PBT and vPvB assessment

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

PBT: Not applicable.




vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures**

Description: Mixture of hazardous substances listed below with nonhazardous additions.

Continue on page 3  
GB

**Trade name: P962 1K ISOLATOR****Dangerous components:**

CAS: 67-63-0	propan-2-ol	50-<60%
EINECS: 200-661-7	 Flam. Liq. 2, H225	
Index number: 603-117-00-0	 Eye Irrit. 2, H319; STOT SE 3, H336	
RTECS: NT 8050000		
Reg.nr.: 01-2119457558-25-0002		
01-2119457558-25-0001		
CAS: 13463-67-7	titanium dioxide	5-<10%
EINECS: 236-675-5	 Carc. 2, H351	
Index number: 022-006-00-2	Note: V, W, 10	

Additional information: For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

General information: Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately rinse with water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contact lenses in case of eye contamination and irrigate copiously with clean water for at least 15 minutes trying to hold the eye lids open.

After swallowing: If symptoms persist consult doctor.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media**

Suitable extinguishing agents:

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

**5.3 Advice for firefighters**

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

**5.6 Fire and explosion Hazards**

Speial protective equipment and fire fighting procedures:

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

**6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

**Trade name: P962 1K ISOLATOR**

Ensure adequate ventilation.

**6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

**7.2 Conditions for safe storage, including any incompatibilities**

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

**7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:

**67-63-0 propan-2-ol**

WEL Short-term value: 1250 mg/m<sup>3</sup>, 500 ppm

Long-term value: 999 mg/m<sup>3</sup>, 400 ppm

Regulatory information WEL: EH40/2020

Additional information: The lists valid during the making were used as basis.

**8.2 Exposure controls**

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Continue on page 5

GB

**Trade name: P962 1K ISOLATOR**

- Penetration time of glove material  
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:  
The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.
- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:  
Rubber gloves
- Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties**

## · General Information

## · Appearance:

- |   |  |
|---|--|
| Form:                                     | Liquid   |
| Colour:                                   | Dark yellow  |
| · Odour:                                  | Characteristic   |
| · Odour threshold:                        | Not determined.  |
| · pH-value at 20 °C:                      | 5-8  |
| · Change in condition                     |  |
| Melting point/freezing point:             | Undetermined.  |
| Initial boiling point and boiling range:  | 82 °C (67-63-0 propan-2-ol)  |
| · Flash point:                            | < 23 °C  |
| · Flammability                            | Highly flammable.  |
| · Autoignition temperature:               | 425 °C   |
| · Decomposition temperature:              | Not determined.  |
| · Ignition temperature:                   | Product is not selfigniting.   |
| · Explosive properties:                   | Risk of explosion by shock, friction, fire or other sources of ignition. |
| · Explosion limits:                       |  |
| Lower:                                    | 2 Vol %  |
| Upper:                                    | 12 Vol %   |
| · Vapour pressure at 20 °C:               | 43 hPa   |
| · Density at 20 °C:                       | 1.034 g/cm <sup>3</sup>  |
| · Relative density                        | Not determined.  |
| · Vapour density                          | Not determined.  |
| · Evaporation rate                        | Not determined.  |
| · Solubility in / Miscibility with water: | Fully miscible.  |
| · Partition coefficient: n-octanol/water: | Not determined.  |
| · Viscosity:                              |  |
| Dynamic:                                  | Not determined.  |
| Kinematic at 20 °C:                       | 0 mm <sup>2</sup> /s   |

**Trade name: P962 1K ISOLATOR**

- Solvent content:
  - Organic solvents: 56.5 %
  - Water: 0.0 %
  - VOC (EC) 589.9 g/l
  - Solids content (volume): 42.9 %
- **9.2 Other information** No further relevant information available.

**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
  - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
  - Acute toxicity Based on available data, the classification criteria are not met.
  - LD/LC50 values relevant for classification:

**67-63-0 propan-2-ol**

- Oral LD50 5,045 mg/kg (rat)
- Dermal LD50 12,800 mg/kg (rabbit)
- Inhalative LC50/4 h 30 mg/l (rat)

**471-34-1 calcium carbonate**

- Oral LD50 6,450 mg/kg (rat)

**9000-59-3 Shellac**

- Oral LD50 >5,000 mg/kg (rat)
- Dermal LD50 >10,000 mg/kg (rab)

**13463-67-7 titanium dioxide**

- Oral LD50 >20,000 mg/kg (rat)
- Dermal LD50 >10,000 mg/kg (rabbit)
- Inhalative LC50/4 h >6.82 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:
  - CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
  - Germ cell mutagenicity Based on available data, the classification criteria are not met.
  - Carcinogenicity Based on available data, the classification criteria are not met.
  - Reproductive toxicity Based on available data, the classification criteria are not met.
  - STOT-single exposure May cause drowsiness or dizziness.
  - STOT-repeated exposure Based on available data, the classification criteria are not met.
  - Aspiration hazard Based on available data, the classification criteria are not met.

**Trade name: P962 1K ISOLATOR**

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

**12.2 Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

**Additional ecological information:**

**General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**12.5 Results of PBT and vPvB assessment**

**PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

**vPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

**12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**European waste catalogue**

HP3 Flammable

HP4 Irritant - skin irritation and eye damage

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP7 Carcinogenic

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

**Recommended cleansing agents:** Water, if necessary together with cleansing agents.

**SECTION 14: Transport information**

**14.1 UN-Number**

ADR, IMDG, IATA

UN1263

**14.2 UN proper shipping name**

ADR

UN1263 PAINT, special provision 640D

IMDG, IATA

PAINT

**14.3 Transport hazard class(es)**

ADR




Class

3 (F1) Flammable liquids.

Continue on page 8  
GB

**Trade name: P962 1K ISOLATOR**

· Label	3
· IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
· <b>14.4 Packing group</b>	
· ADR, IMDG, IATA	II
· <b>14.5 Environmental hazards:</b>	
· Marine pollutant:	No
· <b>14.6 Special precautions for user</b>	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E, S-E
· Stowage Category	B
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, II

**SECTION 15: Regulatory information**

·3YE

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Continue on page 9  
GB

**Trade name: P962 1K ISOLATOR**

## · Hazard pictograms



GHS02 GHS07

## · Signal word Danger

· Hazard-determining components of labelling:  
propan-2-ol

## · Hazard statements

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

## · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

## · Directive 2012/18/EU

## · Named dangerous substances - ANNEX I None of the ingredients is listed.

## · Seveso category P5c FLAMMABLE LIQUIDS

## · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

## · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

## · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

## · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

## · REGULATION (EU) 2019/1148

## · Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

## · Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

## · Regulation (EC) No 273/2004 on drug precursors

108-88-3 toluene: 3

## · Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

108-88-3 toluene: 3

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.**SECTION 16: Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## · Relevant phrases

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.

**Trade name: P962 1K ISOLATOR**· **Classification according to Regulation (EC) No 1272/2008**

---

Flammable liquids

Bridging principles

Serious eye damage/irritation

Specific target organ toxicity (single exposure) method using substance data according to Regulation (EC) No 1272/2008.

The classification of the mixture is generally based on the calculation

· Department issuing SDS: Department of Quality Control

· **Contact:**

HB BODY S.A

Regulatory Officer

Ms Athina Kapourani

Ph: +30 2310 790000

email: a.kapourani@hbbody.com

· \* Data compared to the previous version altered.

**Trade name: P962 1K ISOLATOR****Annex: Exposure scenario****Short title of the exposure scenario****Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Product category** PC9b Fillers, putties, plasters, modelling clay**Process category**

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

**Article category** AC1 Vehicles**Environmental release category** ERC2 Formulation into mixture**Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

**Conditions of use** According to directions for use.**Duration and frequency**

5 workdays/week.

Frequency of use:

**Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

**Physical state** Fluid**Concentration of the substance in the mixture** The substance is main component.**Used amount per time or activity** Smaller than 100 g per application.**Other operational conditions****Other operational conditions affecting environmental exposure**

No special measures required.

Use only on hard ground.

**Other operational conditions affecting worker exposure**

Avoid contact with eyes.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

**Other operational conditions affecting consumer exposure** No special measures required.**Other operational conditions affecting consumer exposure during the use of the product**

Not applicable.

**Risk management measures****Worker protection****Organisational protective measures**

No special measures required.

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

**Technical protective measures**

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Use product only in enclosed systems.

**Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Tightly sealed goggles

**Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

**Environmental protection measures****Water**

No special measures required.

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Continue on page 12

GB

**Trade name: P962 1K ISOLATOR**

Do not allow to reach sewage system.

· **Soil**

The product is only processed over the concrete collecting basin.

Prevent contamination of soil.

· **Disposal measures**

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

· **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

· **Exposure estimation**

· **Consumer**

Not relevant for this Exposure Scenario.

This product is to be used by professional technicians only.

· **Guidance for downstream users**

No further relevant information available.

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.